



Electric Vehicle Charger

Product Features



Screen Display

Equipped with LCM screen to clearly display charging information



Delay Charge

Free to set 1/2/4/8hr automatic delay charging, choose cheap electricity price



Color Light Bar

Convenient for car owners to know the charging state from a distance



Winding Groove Design

Stored the charging gun and wiring neatly for your convenience



Maintenance Hole Design

No need to dismantle the whole machine for maintenance



Emergency Button

Stop charging at any time according to special circumstances



High Standard Safety Protection

When abnormal condition is detected, power will be cut off automatically

Application Place



Car Parks



Residential Area



Restaurants and Hotels



Office Buildings



Tourist Attractions



Vehicle Fleets

Power Specification

		32A		80A	
		Input		Voltage Range AC 220±10V	AC 220±10V
	Input	Input Current	32A	80A	
		Input Power Connect	L, N, GROUND	L, N, GROUND	
		Voltage Range	AC 220±10V	AC 220±10V	
		Frequency Range	60Hz	60Hz	
	Output	Input Current	32A	80A	
		Input Power Connect	7.04kW (Maximum)	17.6kW (Maximum)	
		Physical Specification			
		Connector Type	SAE J1772		
Cable Length	17 FT (5.1M)				
Enclosure Dimension (H*W*D)	L 393.9*W 338.7*H 144.4 (mm)				
Weight	8.6 (KG)				
	User Interface				
	Button	Emergency Button \ Delay Button/Info Button			
	Indicator Light	● Standby : Green	● Charging : Blue	● Complete : Flashing Green	● Fault : Red
	User Identification	RFID (MIFARE CARD)			
	LCM Screen	English			
	Protection				
	Protection	Over-voltage Protection, Over-current Protection, Short-circuit protection, Leakage protection, Overload protection			
	Environmental				
	Operating Temperature	-25°C to +50°C			
	IP	IP 55			
	Humidity	<95%			
	Standard Compliance				
	Standard	CNS15511			

*Specifications may be changed as a result of innovation and improvement and further notice may not be given.



EVALUE Taipei Office

14F., No. 191, Fuxing N. Rd., Songshan Dist.,
 Taipei City 105403, Taiwan (R.O.C.)
 TEL : 886-2-23253320
 FAX : 886-2-23253350
 Customer service hotline : 0800-885-150



EVALUE Website
www.evalue.com.tw

